

CERA PROTETTIVA

SPECIFIC WAX FOR THE POLISHING AND PROTECTION OF
ELITE, ELITE MARMORINO, ELITE VENEZIA.

PRODUCT PROPERTIES

CERA PROTETTIVA is a product based on a mixture of water and solvent suspended waxes. It is a non-filming product that makes the treated surface waterproof, not-yellowing and washing resistant.

IDEAL USES

CERA PROTETTIVA is the specific product to protect and polish "trowel" finishings and stuccos under the Elite Line. It is suitable to protect and polish ELITE, ELITE VENEZIA and ELITE MARMORINO.

TECHNICAL CHARACTERISTICS

SPECIFIC WEIGHT:

0,80 - 0,82 kg/l.

VISCOSITY:

Paste type product.

SPREAD RATE PER COAT:

16 - 20 m²/Kg.

WAY OF USE

APPLICATION:

CERA PROTETTIVA can be applied by trowel in a single coat and thin layer and by pad or cloth.

When the product is well dried polish with a soft cloth. Do not apply on still damp surfaces.

DILUTION:

Ready to use product.

DRYING AT 20°C AND 65% R.H.:

By touch about 60-90 minutes, in depth about 24 hours.

ENVIRONMENTAL CONDITIONS:

The product can be applied at temperatures (of both the environment and/or the surface) between +5°C and +30°C.

TOOLS CLEANING:

With water immediately after use.

SALES PACKAGINGS: 6 x 1 Kg.

SAFETY CAUTIONS:

It is recommended to aerate the rooms during application and before staying in. Store the can well sealed, in a cool place and far away from heat sources.

For further informations refer to the safety data sheet of reference.

NOTES:

This document has been issued at the best of our technical and scientific expertise. Di Donato Spa does not take any responsibility for the results obtained when using this product, since the conditions and application procedures are not controllable by us. Therefore it is advisable to preliminary check the suitability of the product in accordance with the specific case.

